






80G 系列雷达物位计




仪表概述

LR62  应用: 液体 适合强腐蚀性液体、蒸汽、泡沫 测量范围: 0 ~ 30 m 测量精度: ±2mm 过程温度: (-40 ~ 130)°C / (-40 ~ 200)°C 过程压力: (-0.1 ~ 2.5) MPa 频率: 80 GHz 信号输出: (4 ~ 20) mA / HART RS 485 / MODBUS 协议 电源: 24V DC / 220V AC 现场显示 / 按键: 可选 外壳: B / A / D 天线类型: DS / DQ / ES / EQ 天线材料: 316 L + PTFE / 316 L + PFA 安装形式: 法兰 防护等级: IP 67 / IP 66	LR63  应用: 液体 适合强腐蚀性 / 耐压液体 测量范围: 0 ~ 10 m / 0 ~ 30 m / 0 ~ 120 m 测量精度: ±2 mm / ±5 mm 过程温度: (-40 ~ 130)°C / (-40 ~ 200)°C 过程压力: (-0.1 ~ 0.1) MPa (适合耐液体) (-0.1 ~ 2.5) MPa (适合耐压液体) 频率: 80 GHz 信号输出: (4 ~ 20) mA / HART RS 485 / MODBUS 协议 电源: 24V DC / 220V AC 现场显示 / 按键: 可选 外壳: B / A / D 天线类型: AP / AM / FP / FM / FT / GP / GM / GT 天线材料: 316 L + PTFE / PFA 安装形式: 螺纹 防护等级: IP 67 / IP 66	LR64  应用: 液体 卫生级 测量范围: 0 ~ 30 m 测量精度: ±2 mm 过程温度: (-40 ~ 130)°C 过程压力: (-0.1 ~ 1.0) MPa 频率: 80 GHz 信号输出: (4 ~ 20) mA / HART RS 485 / MODBUS 协议 电源: 24V DC / 220V AC 现场显示 / 按键: 可选 外壳: B / A / D / K 天线类型: KW / KQ 天线材料: 316 L + PTFE 安装形式: 2" 卡盘 / 3/4" 卡盘 防护等级: IP 67 / IP 66	LR65  应用: 固体 / 液体 存储容器 / 过程容器或强粉尘场合 测量范围: 0 ~ 120 m 测量精度: ±5 mm 过程温度: (-40 ~ 110)°C / (-40 ~ 130)°C (-40 ~ 200)°C 过程压力: (-0.1 ~ 0.1) MPa / (-0.1 ~ 0.3) MPa 频率: 80 GHz 信号输出: (4 ~ 20) mA / HART RS 485 / MODBUS 协议 电源: 24V DC / 220V AC 现场显示 / 按键: 可选 外壳: B / A / D 天线类型: MW / NW / RW / HG / JG / LG 天线材料: 铝衬塑料 + PP / 316 L + PTFE / 316 L 316 L + PTFE 带散热 / 316 L 安装形式: 法兰 / 螺纹 / 吊架 防护等级: IP 67 / IP 66
---	--	--	---

天线

型号								
	DS/ES(LR62)	DQ/EQ(LR62)	AP/AM(LR63)	FP/FM(LR63)	FT(LR63)	GP(LR63)	GM(LR63)	GT(LR63)
材料	316L+PTFE 316L+PFA	316L+PTFE	PFA /316L+PTFE	PFA /316L+PTFE	316L+PTFE	PFA	316L+PTFE	316L+PTFE
过程连接	DN50/80/100 DN80/100/125/150	DN50/80/100 DN80/100/125/150	螺纹 G 3/4 A 螺纹 1/2 NPT	螺纹 G 1 1/2 A 螺纹 1 1/2 NPT	螺纹 G 1 1/2 A 螺纹 1 1/2 NPT	螺纹 M80X3	螺纹 G3A	螺纹 G3A
特点	防腐 / 高压 / 130°C	防腐 / 高压 / 散热 /200°C	防腐 / 130°C / 高压 / 130°C	防腐 / 130°C / 高压 / 130°C	高压 / 散热 /200°C	防腐 / 130°C	高压 / 130°C	高压 / 散热 /200°C

天线

型号								
	KW(LR64)	KQ(LR64)	MW(LR65)	NW(LR65)	RW(LR65)	HG(LR65)	JG(LR65)	LG(LR65)
材料	316L+PTFE	316L+PTFE	铝衬塑料 + PTFE 铝衬塑料 + PP	316L+PTFE 316L+PP	316L+PTFE	铝衬塑料 + PTFE 铝衬塑料 + PP	316L+PTFE 316L+PP	316L+PTFE
过程连接	2" 卡盘	3/4" 卡盘	DN100/125/150	DN100/125 /150	DN100/125 /150 / 吊架	DN80/100/125 /150	DN100/125 /150	DN100/125 /150
特点	卫生级 / 130°C	卫生级 / 130°C	万向 / 吹扫 / 110°C	万向 / 吹扫 / 130°C	万向 / 吹扫 / 散热 /200°C	螺纹 / 吹扫 / 110°C	螺纹 / 吹扫 /130°C	螺纹 / 吹扫 / 散热 /200°C